

### JLG\* Rough Terrain REACHING OUT

On the job site, days are measured by productivity. Your productivity. Which means you need equipment that stands up to the day's demands. JLG has what you need so you can put in the most productive day possible. Scissor lifts that can handle more workers and supplies in one shot.

Whether you're treading on slab or off,

JLG® Scissor Lifts provide superior performance
and reliability. Our engine powered scissor
lifts deliver exceptional terrainability and
gradeability. JLG RT Scissor Lifts have the
capacity to accommodate both workers and our
exclusive Workstation in the Sky® accessories.

Give your day's productivity a major boost upward with JLG Rough Terrain Scissor Lifts.

# UNLEASH MACHINES THAT DRIVE YOUR PERFORMANCE HIGHER





## NARROW DESIGN, EASY MOBILITY

With standard four-wheel drive, rugged lug tread tyres and 35% gradeability, you'll be able to keep work moving, on or off slab. The 260MRT compact scissor lift delivers exceptional mobility thanks to a narrow 1.75 m chassis that gets you into those challenging spots.

A large work platform with a 1.22 m roll-out deck extension keeps everything you need within arm's reach. Simplified ground control wiring and built-in diagnostics are provided for serviceability.

### HIGHER CAPACITIES, BIGGER PLATFORMS

The powerful RT Series lets you work more efficiently on the job, over a range of applications, with increased lift capacities, bigger platforms and a choice from 12.6 m to 18.3 m working height. When you want to finish on time and on budget, put the RT Series to work for you. The exclusive MegaDeck® platform gets more people and materials up to your work area for optimum productivity and provides over 13.5 m of work space. This is critical when you have applications requiring multiple sheets of drywall or siding.

Set up quickly and efficiently with the optional one-touch leveling jacks. With an average leveling time of 15 to 30 seconds, you can cut set up time by 100% compared to other scissor lifts.





**4WD**The 260MRT features
standard four-wheel drive
with 35% gradeability.




Capacity
The 260MRT provides
improved scissor rigidity and
a large deck space with a
capacity of 570 kg maximum.



Terrainability
Up to 45% gradeability
and hydrostatic 4-wheel
drive delivers unmatched
terrainability.



**Leveling Jacks**Faster leveling capabilities with optional one-touch leveling jacks.



### MAIN FEATURES

- 4-Wheel Drive
- AutomaticTransmission
- AC Powercable to Platform
- Self-Closing Entry Gate

|                                    | 260MRT            |  |  |
|------------------------------------|-------------------|--|--|
| Rough Terrain Scissor Lifts        |                   |  |  |
| Platform Height                    | 7.92 m            |  |  |
| Platform Capacity                  | 570 kg            |  |  |
| Capacity on Extension              | 140 kg            |  |  |
| Platform Size                      | 1.65 x 2.59 m     |  |  |
| Overall Width                      | 1.75 m            |  |  |
| Weight                             | 3,390 kg          |  |  |
| Diesel Engine – Kubota D1005       | 23.5 hp (17.5 kW) |  |  |
| Available Options                  |                   |  |  |
| Flashing Amber Beacon              |                   |  |  |
| Leveling Jacks                     |                   |  |  |
| Platform Worklights                |                   |  |  |
| 13 mm Air Line to Platform         |                   |  |  |
| 1.22 m Manual Front Deck extension |                   |  |  |

|                                     | 3394RT                                    | 4394RT                                    | 5394RT                             |
|-------------------------------------|---|---|------------------------------------|
| Rough Terrain Scissor Lifts         |   |   |                                    |
| Platform Height                     | 10.06 m                                   | 13.11 m                                   | 18.3 m                             |
| Platform Capacity                   | 1,020 kg                                  | 680 kg                                    | 680 kg                             |
| Capacity on Extension               | 225 kg                                    | 225 kg                                    | 227 kg                             |
| Capacity w/Dual Extensions          | 905 kg                                    | 565 kg                                    | 680 kg                             |
| Platform Size                       | 2.18 x 3.81 m                             | 2.18 x 3.81 m                             | 1.87 x 3.96 m                      |
| Overall Width                       | 2.39 m                                    | 2.39 m                                    | 2.31 m                             |
| Weight                              | 6,600 kg                                  | 7,100 kg                                  | 7,994 kg                           |
| Engine                              | Diesel Engine - Deutz<br>D2011L03 36.4 kW | Diesel Engine - Deutz<br>D2011L03 36.4 kW | Kubota Diesel<br>D1305-E3B 21.7 kW |
| Available Options                   |   |   |                                    |
| Flashing Amber Beacon               |   |   |                                    |
| Leveling Jacks                      |   |   |                                    |
| Platform Worklights                 |   |   |                                    |
| 13 mm Air Line to Platform          |   |   |                                    |
| 1.22 m Powered Dual Deck extensions |   |   |                                    |
| 1.22 m Manual Rear Deck extension   |   |   |                                    |



### MAIN FEATURES

- Oscillating front axle
- 4-Wheel Drive
- Automatic transmission
- AC Powercable to platform
- Self-Closing entry gate

6

### Deutschland

Tel: +49 (0) 421 693 5000 JLG Deutschland GmbH Max-Planck-Straße 21

D-27721 Ritterhude/Ihlpohl (Bei Bremen)

### España

Tel: +34 93 772 47 00 JLG Ibérica, SL Trapadella, 2 Pol. Ind. Castellbisbal Sur

08755 Castellibisbal (Barcelona)

### France

Tel: +33 (0) 553 88 31 70
JLG France SAS
ZI Guillaume mon Amy
CS 30204 Fauillet
F-47400 Tonneins

### Italia

Tel: +39 02 9359 5210 JLG Industries (Italia) s.r.l. Via Po.22 20010 Pregnana Milanese -MI-

### Russia

Tel: +7 (495) 967 79 14

JLG Industries Inc.

Vashutinskoe shosse 24b

Khimki, Moscow Region 141400

Russian Federation

### Sverige

Tel: +46 (0) 8 506 59500 JLG Sverige AB Enköpingsvägen 150 Box 704, SE-176 77 Järfälla

### **United Kingdom**

Tel: +44 (0) 161 654 1000

JLG Industries (United Kingdom) Limited
Bentley House, Bentley Avenue
Middleton, Greater Manchester

M24 2GP

### JLG EMEA BV

Tel: +31 (0) 23 565 5665 Polaris Avenue 63 2132 JH Hoofddorp The Netherlands

### JLG Manufacturing Europe byba

Tel: +32 (0) 89 77 49 74 Oude Bunders 1034 Breitwaterstraat 12a B-3630 Maasmechelen Belgium

### Romania Manufacturing Central Europe SRL

Tel: +40 (0) 269 803 974 A. Vlaicu nr. 41 551041 Medias



### JLG Industries, Inc. is a leading designer and manufacturer of access equipment and complementary services and attachments.

JLG has manufacturing facilities in the United States, France, Romania, China and Belgium. Customers throughout Europe, Africa and the Middle East benefit from a network of dedicated sales and service operations designed to deliver the highest levels of support.



www.jlg.com JLG is an Oshkosh Corporation company.